

P330

4K 8MP Smart PoE IP Camera with Person/Vehicle Detection & Clear Night Vision

- 4K 8MP Ultra HD
- Person/Vehicle Detection
- IP66 Waterproof

Specifications

Video & Audio	
Image Sensor	1/2.7" CMOS Sensor
Video Resolution	3840x2160 (8.0 Megapixels) at 25 frames/sec
Lens	f=2.8mm fixed; F=1.6, with IR-cut filter
Videoformat	H.265
Field of View	• Horizontal: 105° • Vertical: 56°
Day & Night	Auto-switching with IR-cut filter
Infrared Night Vision	30 meters (100ft) (LED: 2pcs/1.8w/850nm)
Color Night Vision	Spotlight: 1pc/4.3W/6500K/700 Lumens
Power	
PoE	IEEE 802.3af, 48V Active
DC Power	DC 12.0V 1A, <12W
Interface	
Power	DC power port

System	Reset button
Ethernet	One 10M/100Mbps; RJ45
Storage	microSD card slot (support up to 512GB)
Audio	
Two-Way Audio	Built-in microphone and speaker
Software Features	
Frame Rate	• Mainstream: 2fps - 25fps (default: 25fps) • Substream: 4fps - 15fps (default: 10fps)
Code Rate	Mainstream: 2048Kbps - 8192Kbps (default: 6144Kbps) Substream: 64Kbps - 512Kbps (default: 256Kbps)
Browser Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection; person detection; vehicle detection; Animal Detection
Record Modes	Motion-triggered recording (default); scheduled recording; 24/7 recording
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	20 users (1 admin account & 19 user accounts); support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Smart Home	Google Assistant
Working Environment	
Temperature	Operating temperature: -10°C - +55°C (14°F - 131°F)
Humidity	Operating humidity: 10% - 90%
Weatherproof	IP67 rated
Size & Weight	

Dimension	68 x 63 x 188mm
Weight	452.4g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



1. Mount
2. Metal Aluminum Case
3. 18 IR LEDs
4. High Definition Lens
5. Daylight Sensor



1. Power
2. Reset Button
3. Network
4. Waterproof Lid
5. Daylight Sensor



1. Unscrew it (counterclockwise) to loosen the bracket and adjust the camera in any direction.
2. After adjustment, twist it back to fix the camera.

